



| Key Largo | |
|-----------|--|
| | |
| | |

Exp. Date: 10/13/2012 **Quote No:** 11/07/2012 10608-0004

Page 1

| 11/07/2012 | | Page I |
|------------|--|--------|
| PART NO | DESCRIPTION | QTY |
| | == Legals - Aerial - 1205.001 05/08/12 == | 1 |
| 02-B2-1420 | Tilt Table | 1 |
| 02-B2-1425 | Tilt Table Test | 1 |
| 02-H2-2020 | Drawings - Approval | 1 |
| 02-K2-0220 | Pre-Construction Conference - Factory | 1 |
| 02-K4-0220 | Final Inspection - Factory | 1 |
| | == Ferrara Intruder Ember - Aerial Chassis - 2.801 == | 1 |
| 00-00-0010 | NFPA-1901, 2009 Edition - Incomplete Chassis | 1 |
| 00-00-009F | Vocation and Basic Attributes - Ferrara Intruder Chassis | 1 |
| 00-00-902F | Paint Codes and Basic Attributes - Ferrara Intruder Chassis | 1 |
| | CHASSIS | 1 |
| 00-J0-0102 | Ferrara Intruder Ember Series Tilt Cab & Chassis | 1 |
| 00-J0-2000 | I Custom Firetruck Chassis | 1 |
| 01-B0-0110 | 4x2 Chassis - SA Aerial - MFS Frt - FFA | 1 |
| 01-H0-1600 | I Double Frame Rails | 1 |
| 01-J0-4000 | I Cab Main Frame Crossmember | 1 |
| 07-A0-2022 | I Front Axle 21,500# - Meritor MFS | 1 |
| 07-AC-4500 | 45° Cramp Angle | 1 |
| 07-B0-0100 | I Oil Seals - Front Axle - Factory Premium | 1 |
| 07-C0-0100 | I S-Cam Brakes - Front Axle | 1 |
| 07-R0-1022 | l Front Suspension 21,500# - Semi-Elliptical Spring | 1 |
| 07-RS-0100 | I Shock Absorbers - Front Axle | 1 |
| 07-Y0-0122 | I Steering - 21,500# - Sheppard Dual Gear | 1 |
| 10-GF-2100 | I Goodyear 425/65R22.5-20PR (L) Front - G296 - 24,600#-26,320# | 1 |
| 10-GG-0044 | I 22,800# - Std Load Rating G296 425/65R22.5 L | 1 |
| 10-GV-0065 | I Tire Speed Rating - 65 MPH | 1 |
| 10-W0-1040 | I Front - Aluminum Wheels - 13.00 | 1 |
| 10-X0-0100 | I Stainless 'Baby Moon' Caps & Nutcovers | 1 |
| 08-AS-2132 | I Single Rear Axle 33,000# - Spicer S35 - FFA | 1 |
| 08-B0-0100 | I Oil Seals - Rear Axle - Factory Premium | 1 |
| 08-C0-0100 | I S-Cam Brakes - Single Rear Axle | 1 |
| 08-PA-0090 | Vehicle Top Speed Less Than 60 MPH | 1 |
| 08-R0-0120 | Single Axle Suspension - 34,000# - Spring | 1 |
| 09-A0-1110 | l Air System - Color Coded Nylon Air Lines - Single Axle - FFA | 1 |
| | | |
| | | |

| PART NO | DESCRIPTION | QTY |
|----------------|--|-----|
| TILLET TO | | LIV |
| 09-A0-1208 | Bendix AD SP Dryer | 1 |
| 09-D0-0102 | Air Tank Drains - Manual | 1 |
| 09-L0-0400 | I ABS Brake System - 4 Wheel - Meritor/Wabco | 1 |
| 10-GT-3500 | l Goodyear 315/80R22.5-20PR (L) Rear - G291 - 35,400# | 1 |
| 10-GV-0068 | Tire Speed Rating - 68 MPH | 1 |
| 10-W0-3020 | Inner and Outer Rear - SA - Aluminum Wheels - 9.00 | 1 |
| 10-X0-0300 | I Stainless "Lincoln Hat" Hub & Nut Covers | 1 |
| 08-RS-0500 | Axle & Chassis Laser Alignment | 1 |
| 10-GW-0122 | Tire Pressure Monitoring Device - 2 Axles - LED Alert | 1 |
| 13-FV-6403 Cum | nmins ISL9 - 400 HP - EPA13 - Intruder Ember - 1200 Rad | 1 |
| 13-A0-1200 | Engine Cooling System Radiator - 1200 Sq. In. | 1 |
| | l Engine Coolant Recovery System | 1 |
| 13-A0-1500 | l Charge Air Cooler - Engine Air Intake | 1 |
| 13-A0-1700 | l Radiator Coolant | 1 |
| 13-A0-1910 | l Silicone Cooling System Hoses | 1 |
| 13-A0-1960 | l Constant Torque Cooling System Clamps - Entire System | 1 |
| 13-A0-1974 | Heater Shut Off Valves | 1 |
| 13-L0-0002 | Engine Oil - First Fill | 1 |
| | Engine Brake - Cummins ISL Engine | 1 |
| | Fast (High) Idle - Manual Select - Auto Low Voltage | 1 |
| | · Corrosion Inhibitor | 1 |
| 13-V0-0120 | Auxiliary Engine Cooler - Sendure | 1 |
| 13-V0-0210 | | 1 |
| 13-V0-3000 | Fan Clutch | 1 |
| 13-Y0-0520 | EPA 2010/2013 Compliant Exhaust Treatment System - ISC/ISL | 1 |
| | l Cummins Aftertreatment System - EPA10 - ISC/ISL | 1 |
| | l Stainless Tailpipe - Curb Side - 90° Exit - Straight Cut End | 1 |
| 13-Y0-6010 | l Exhaust Tailpipe Diffuser | 1 |
| 13-Z0-0010 | DEF System - 5 Gallon Reservoir - EPA10 | 1 |
| 14-C0-3000 | Allison 3000EVS Automatic Transmission | 1 |
| 14-D0-0200 | l Synthetic Transmission Fluid - Allison TES-295 | 1 |
| | l Five Speed Allison Programming - 3000EVS | 1 |
| | l Automatic Neutral Programming - 3000EVS / 4000EVS | 1 |
| | · 1760 Series Drivelines | 1 |
| 14-W0-1802 | l Temporary Installed Drivelines | 1 |
| | Fuel Tank - 50 Gallon | 1 |
| 25-V0-0000 | Reinforced Fuel Lines | 1 |
| 25-V0-1102 | l Fuel Shut Off Valve | 1 |
| 25-F0-0200 I | Fuel Filter - Cummins - Factory | 1 |
| | · 320 Amp Alternator - Leece-Neville - 4890JB | 1 |
| | CAB MODEL | 1 |
| 40-CE-0014 MFI | Oxl - FFA Intruder Ember - NOTCHED 12" Extended Fwd | 1 |
| Exte | nded Forward Raised Roof - Notched for Aerial Application | |
| | | |
| 14-ES-0200 | Transmission Selector - Push Button Type | 1 |
| | l Transmission Fluid Check - Transmission Selector | 1 |
| | EMI/RFI Noise Supression | 1 |
| | Stainless Steel Battery Tray | 1 |
| | Single Battery System - 4 Group 31 - Ferrara | 1 |
| | 40 Amp - Kussmaul - Auto Charge 1200 | 1 |
| | · · | |

| 11/07/2012 | | Page 3 |
|--------------------------|--|--------|
| PART NO | DESCRIPTION | QTY |
| 45-T0-6114 | Kussmaul Remote Charge Indicator - Kussmaul Charge | 1 |
| 45-T0-6210 | l Charge Indicator Panel on Driver's Seat Box | 1 |
| 45-Z0-1200 | Kussmaul 20 AMP - 120v - Super Auto Eject | 1 |
| 45-Z0-1302 | I Yellow Auto-Eject Cover | 1 |
| 45-Z0-1320 | l Cab Exterior Mounted - Behind the Driver's Door | 1 |
| | CAB INTERIOR | 1 |
| 40-D0-5018 | Cab Interior Appointments and Options - Intruder Ember | 1 |
| 40-DE-0100 | I Engine Enclosure - Vinyl Covering | 1 |
| 40-DE-1030 | I Painted Interior Door Panels | 1 |
| 40-DE-2010 | I Interior Padding - Standard Ceiling | 1 |
| 40-DE-2020 | l Interior Padding - Standard Rear Wall | 1 |
| 40-DE-2060 | Floor Material - Accoustical Wear Mat | 1 |
| 40-DE-2070 | * * Rear Facing Seat Box Covering - Accoustical Wear Mat | 1 |
| 40-DE-4002 | I Cab Step Well Trim - Step Tops Only | 1 |
| 40-DH-0240 | l Grab Hndls - Inside - Officer's A-Post and Both Crew Doors | 1 |
| 40-DH-1220 | Officer's Radio Compartment With Door | 1 |
| 40-DS-4120 | Full Width Intermediate Front Step - 100" Cab | 1 |
| 40-DS-4210 | Cab Crew Area Foot Rest - 100" Cab | 1 |
| 40-DS-4210 40-LC-0114 | | 1 |
| 40-LC-0114 40-LD-0099 | l Open Compartment Light - Red Flashing - Whelen OS LED l Interior Lighting Group - Ember Series | 1 |
| 40-LD-0099 40-LD-1104 | * * * | 1 |
| 40-LD-1104 40-LD-2168 | Two (2) 7" Clear Dome Lights | 1 |
| 40-LD-2108 40-U0-0104 | Four (4) White / Red LED Dome Lights Overhead Heater / Defroster - Intruder | 1 |
| 40-U0-0104 40-U0-0450 | | 1 |
| 40-U0-0430 40-U0-0610 | 45,000 BTU Air Conditioning with Heater - Single Condenser | 1 |
| 40-U0-0620 | 36,000 BTU Supplemental Heater | 1 |
| | Cab Climate Control Insulation Package | 1 |
| 40-V0-0104 | Driver Instrumentation (J1939) and Controls - Intruder | 1 |
| 40-V0-0120 | Audible Turn Signal Reminder | 1 |
| 40-V0-0122 | Audible Lights On Reminder | 1 |
| 40-V0-0124 | Audible Parking Brake Reminder | 1 |
| 40-V0-0130 | Dual Trip Odometers | 1 |
| 40-V0-0148 | Odometer Activated While in Pump Mode | 1 |
| 40-V0-0150 | Low Fuel Warning Light and Alarm | 1 |
| 40-V0-0152 | Transmission Temperature Warning Light and Alarm | 1 |
| 40-V0-0154 | Low Voltage Warning Light | 1 |
| 40-V0-0156 | Air Cleaner Restriction Indicator | 1 |
| 40-V0-0160 | Low Coolant Warning | 1 |
| 40-V0-0162 | Wiper Control, Intermittent | 1 |
| 40-X0-0214 | l Overhead Switch Panel (13 Individual 1 Master) - Ferrara | 1 |
| 40-V0-0502 | Parking Brake Control - Driver's Dash | 1 |
| 45-NS-0104 | Apparatus Base Analog Electrical System - Ferrara | 1 |
| 40-Z0-0010 | 12 VDC Power Point Socket | 1 |
| 40-Z0-0012 | Battery Direct Power | 1 |
| 40-Z0-0120 | Location - Officer's Side | |
| 40 D0 (210 | CAB EXTERIOR | |
| 40-D0-6218 | Cab Ext Appointments & Options - Intruder Ember - Aerial | |
| 40-D0-0900 | Cab Crashworthiness Test | |
| 40-DH-2100 | Exterior Grab Handles - 24" Long | |
| 40-DZ-0122 | I Ferrara Front Grille - Cast Assembly | |
| 40-G0-1110 | l Cab Ground Lights | |
| | | |

| 11/0//2012 | | rage 4 |
|--------------------------|--|--------|
| PART NO | DESCRIPTION | QTY |
| 40-J0-1500 | I Heated and Remote Controlled Moto-Mirror with Lower Convex | 1 |
| 40-K0-1000 | I Cab Side Windows - Fixed Glass | 1 |
| 40-K0-2020 | l Electric Windows - Four Doors - Driver Additional Controls | 1 |
| 40-LE-1002 | I Engine Maintenance Lights - Custom | 1 |
| 40-N0-0810 | I Cab Stainless Fender / Stainless Wheel Well Liner | 1 |
| 40-N0-1400 | l Exterior Rear Wall - Diamondplate Overlay | 1 |
| 40-P0-0210 | l Cab Tilt - Electric Pump with Manual Back Up - FFA Aerial | 1 |
| 40-P0-0400 | Cab Tilt Road Interlock | 1 |
| 40-P0-1710 | Cab Tilt - Aerial Interlock | 1 |
| | CAB AND CHASSIS PAINT | 1 |
| 40-Q0-1006 | Cab & Chassis Paint - Intruder | 1 |
| 40-Q0-1010 | I Black Gloss Enamel Painted Frame | 1 |
| 40-Q0-1206 | Gray Interior Paint - Intruder | 1 |
| 40-Q0-2012 | Headliner - Gray | 1 |
| 40-Q0-2012 40-Q0-2112 | Rear Wall Covering - Gray | 1 |
| 40-Q0-2112 | Real Wall Covering - Gray Floor Covering - Gray | 1 |
| 40-Q0-2212 40-Q0-2312 | • | 1 |
| _ | | 1 |
| 40-Q0-2502 | Dash Housing and Officer Console - Black | 1 |
| 40-Q0-3020 | I Two-Tone Cab Exterior Paint | 1 |
| 40-Q0-3070 | Cab Exterior Paint - Dupont - Urethane | 1 |
| 40-Q0-3100 | 5 Year Cab Paint Warranty | |
| 10 70 7002 | SEATING | 1 |
| 40-RS-5003 | Intruder - MFDxl - 2 Rear Facing | 1 |
| 40-S0-0510 | l Intruder Seat Position 1 - Driver's Seat | 1 |
| 40-S0-1150 | l Highback - Air Ride Suspension - HO Bostrom | 1 |
| 40-S0-8110 | l Red - Shoulder Harness - Seat Belt | 1 |
| 40-S0-0520 | l Intruder Seat Position 2 - Officer's Seat | 1 |
| 40-S0-4110 | I SCBA Fixed Bottom Cushion - Fixed Mounting - HO Bostrom | 1 |
| 40-S0-8110 | Red - Shoulder Harness - Seat Belt | 1 |
| 40-S0-9120 | I HO Bostrom SecurAll SCBA Locking Bracket | 1 |
| 40-S0-0530 | l Intruder Seat Position 3 - Rr Facing Left Outbrd - Behnd Drv | 1 |
| 40-S0-5512 | RR Out SCBA - Fixed Bottom Cushion - Fixed Mounting - HO Bostrom | 1 |
| 40-S0-8120 | Red - Lap Type Belt - Seat Belt | 1 |
| 40-S0-9120 | HO Bostrom SecurAll SCBA Locking Bracket | 1 |
| 40-S0-0560 | l Intruder Seat Position 6 - Rr Facing Rt Outbrd - Behind Offi | 1 |
| 40-S0-5512 | RR Out SCBA - Fixed Bottom Cushion - Fixed Mounting - HO Bostrom | 1 |
| 40-S0-8120 | Red - Lap Type Belt - Seat Belt | 1 |
| 40-S0-9120 | HO Bostrom SecurAll SCBA Locking Bracket | 1 |
| 40-S0-752F | I Intruder Seat Covers - Gray - No HME Logos | 1 |
| | No HME Logos | |
| | | |
| 40-S0-7320 | Durawear Seat Covering - HO Bostrom | 1 |
| 40-S0-8002 | I Seat Belt Warning Labels | 1 |
| 40-S0-8014 | Vehicle Data Recorder and Seat Belt Warning System | 1 |
| 40-S0-8014 40-S0-8016 | Seat Belt Warning System Monitor Panel | 1 |
| 10-20-0010 | FRONT BUMPER / AUDIBLE WARNING | 1 |
| 42-A0-2016 | Front Bumper - 12" High - Polished Stainless - Intruder | 1 |
| 01-V0-3323 | | 1 |
| | Front Bumper Extension - 24 Inches - Intruder | 1 |
| 01-W0-0700 | Chromed Tow Hooks Beneath Bumper | |
| 01-Z0-8012 | l Front Gravelshield | 1 |
| | | |

| 11/0//2012 | | Page 5 |
|------------|---|--------|
| PART NO | DESCRIPTION | QTY |
| 01-Z0-8202 | l Center Hosewell | 1 |
| 40-H0-1108 | l Dual Stutter Tone Air Horns - OUTBOARD - Ferrara | 1 |
| 40-H0-1201 | Air Horn Circuit Powered - Battery and Ignition | 1 |
| 40-H0-1210 | Air Horn Control - Lanyard | 1 |
| 40-H0-1310 | Vehicle Horns / Electronic Siren Selector Switch | 1 |
| 40-HA-2020 | l Siren Speaker - Cast Products - Recess Mtd - Left Side | 1 |
| 69-C0-0202 | l Electronic Chassis Operator's Manual w/Parts List - Two Sets | 1 |
| | Lighting Selections | 1 |
| | Intruder Ember - Cab & Chassis Headlights, ICC Lighting | 1 |
| 55-02-1004 | Custom Cab - Cab - LED - ICC Lighting - Intruder Ember | 1 |
| 55-03-0102 | Headlights - Halogen - Intruder Ember | 1 |
| 55-03-0112 | Daytime Running Headlights - Intruder Ember | 1 |
| 55-04-0310 | Frt Turn Signal - LED - Intruder Ember | 1 |
| 57-20-8304 | Cab, Front Warning, Whelen - Super LED - Intruder Ember | 1 |
| | | 1 |
| 62-01-0100 | Temporary Chassis Rear Taillights and Mud Flaps | 1 |
| 75 AF 0200 | Bodybuilder Items | 1 |
| 75-AF-0200 | ~Ferrara Aerial Interface | 1 |
| 99-99-1000 | HME to do MVP cab notch | 1 |
| 99-99-2000 | Chassis Discount | 1 |
| | v2.810 - RELEASE DATE - 09/19/2012 | 1 |
| | == Chassis Mods - OTHER MFG / STOCK - 1205.001 05/08/12 == | 1 |
| 03-M0-0000 | Carrying Capacity Plate - NFPA | 1 |
| 03-M2-0620 | I Plate - Seating Capacity - 4 People | 1 |
| 03-M4-0220 | Plate - Occupancy/Seat Belt | 1 |
| 03-M4-0420 | Label - "Do Not Wear Helmet While Seated" | 1 |
| 03-M4-0620 | Plate - Overall Height/Length/Weight | 1 |
| 03-M4-0820 | Plate - Fluid Capacity | 1 |
| 03-M4-1020 | Plate - Apparatus Movement Warning | 1 |
| 03-M4-1220 | Plate - Occupancy - Do Not Ride | 1 |
| 03-M8-0620 | Manuals on CD | 1 |
| 04-H4-2220 | Mud Flaps - Front - Black | 1 |
| 06-B6-6260 | Mud Flaps - Rear - Black | 1 |
| 07-00-0000 | FFA Switches | 1 |
| 07-00-0000 | Replace all HME supplied rocker switches in overhead switch panel with FFA switches used in | 1 |
| | Igniter/Inferno | |
| | igniter/interno | |
| 00 D0 0420 | Alla Tullet Assertitions Defende Com W. II | 1 |
| 08-B8-0420 | Air Inlet - Auxiliary - Driver's Step Well | 1 |
| 10-A6-0220 | Tow Eyes - Chrome Plated - Below the Bumper | 1 |
| | Remove HME supplied tow hooks and replace with chrome tow eyes | |
| | | |
| 12-G2-6020 | I Transmission - Lock-Up - EVS3000 | 1 |
| 16-D2-0620 | Exterior Trim - Rear Stepwell - ATP - w/ Battery Access Hinged Doors | 1 |
| 16-J2-0420 | Console - Aluminum - Custom | 1 |
| | Custom center console | |
| | | |
| | Match H-5022 Davie | |
| | | |
| | Remove siren from engine cover and install in center console | |
| | | |
| 16-J8-0420 | Reflective Material - (4) Lower Interior Door Panels | 1 |
| 20000120 | Use lime green 3M reflective striping | 1 |
| | ose time green switcheenve surping | |

| 11/0//2012 | | rage 0 |
|--------------|--|--------|
| PART NO | DESCRIPTION | QTY |
| 18-K2-0220 | Compartment - EMS - Inboard Forward Facing | 1 |
| | 48"W x 48"H x 22"D | |
| | | |
| 18-K2-0620 | l Door - EMS Compartment - Roll-up | 1 |
| 18-K2-2020 | I Anodized Aluminum Sill Plates | 1 |
| 18-K4-0620 | l Light - (1) Compartment - 36" Night Stik - Access 73036 | 1 |
| 18-K6-0220 | Shelf - (1) | 1 |
| 20-A2-0720 | Blue Sea Fuse Block #5025 (6) Place (ea) | 1 |
| 20-112-0120 | Mount behind officer seat | 1 |
| | Would belind officer seat | |
| 20 44 4920 | C' I'I' EMOD M 4 1 | |
| 20-A4-4820 | Cigar Lighter - EMS Box Mounted | 2 |
| | Mount both on top of EMS box | |
| | | |
| | Wire to battery hot | |
| | | |
| 20-G4-0420 | Lights - Cornering - LED | 1 |
| | Replace HME supplied red cornering lights with Whelen Linear LED model# 40R02ZRR | |
| | | |
| | Program flash pattern to SingleFlash 90 | |
| | | |
| 21-00-0000 | Restraining Strap - Compartment - Center | 1 |
| 21 00 0000 | Add to center bumper compartment | 1 |
| | And to center bumper compartment | |
| 22-D6-0220 | Comerc Federal Signal Model CAMSETTO 7" Color Dignley | 1 |
| | Camera - Federal Signal Model - CAMSET70 - 7" Color Display | 1 |
| 70-07-0600 | Siren - Whelen - WS-295HFS2 Hand Free | 1 |
| | == Pump Enclosure - Aerials - MVP - 1205.001 05/08/12 == | 1 |
| 20-A2-1220 | PUMP MODULE - SIDE MOUNT EXTRUDED ALUMINUM | 1 |
| 20-A4-2220 | Separate Pump Module - Extruded | 1 |
| 20-C4-0620 | Pump Panels - Brush Stainless Steel | 1 |
| 20-D6-0220 | Light - Pump Panel (1) Left Side - Night Stik Access LED 36" | 1 |
| 20-D6-1220 | l Light - Pump Panel (1) Right Side - Night Stik Access LED 36" | 1 |
| 20-D8-0220 | Light - Pump Compartment (1) | 1 |
| 20-F8-0220 | Platform - Pump Operator's - Slide-Out (500 LB.) | 2 |
| 20-H4-0820 | Switch - Pump Panel - Air Horn | 1 |
| 20 11 1 0020 | 5 when Tump Tuner Tin Hern | |
| | | |
| | | |
| | | |
| | DUCH DUTTON CTVI E | |
| | PUSH BUTTON STYLE | |
| 20.16.0220 | | |
| 20-J6-0220 | Gauges - Pressure 2-1/2" Metal Face w/ Thuemling Bezels | 1 |
| 20-J6-6220 | Bezels - Standard Colors | 1 |
| 20-M4-0220 | Tags - Pump Panel - Color Coded (METAL) | 1 |
| 22-A4-0620 | I Pump System - Waterous - CS 750-1250 GPM S/S | 1 |
| 22-F4-0420 | Mechanical Seal - CS/CM/CSU/CMU | 1 |
| 22-G2-0220 | Pump Shift - Dash Mounted | 1 |
| 22-J4-0220 | Primer - Waterous - VPO Electric - Oil less | 1 |
| 22-R2-0420 | I U.L. Test Points | 1 |
| 22-R2-1620 | U.L. Certification 1250 GPM | 1 |
| 22-R4-0420 | Certification Plate - Pump Test | 1 |
| | . Common rate ramp rost | |
| | | |

| 11/07/2012 | | Page 7 |
|--------------------------|--|--------|
| PART NO | DESCRIPTION | QTY |
| 22-S4-0220 | I Warranty - Waterous Pump 5 Years (Parts) | 1 |
| 22-S8-0220 | I Manuals - Pump | 1 |
| 24-A4-4020 | I Suction Header - LS 6" w/Long Handle Cap | 1 |
| 24-B4-4020 | I Suction Header - RS 6" w/Long Handle Cap | 1 |
| 24-J8-0420 | Relief Valve - Intake - Akron 59 | 1 |
| 20-J4-1620 | Pressure Governor - Pump Boss - FRC - PBA401-D00 | 1 |
| 20-J2-0220 | I Gauges - Master 4-1/2" Suction / Pressure Metal Face | 1 |
| 32-E2-2020 | I Return Line - Fill Subsurface | 1 |
| 24-R2-0420 | Tank-To-Pump - 3" Push-Pull | 1 |
| 22-P2-0620 | I Valve - Master Drain - Midship Pump | 1 |
| 24-S6-0420 | I Tank Fill - 1-1/2" - Push-Pull | 1 |
| 24-T2-0420 | I Cooler - Engine - 1/4 Turn | 1 |
| 24-T2-0620 | I Cooler - Pump - 1/4 Turn | 1 |
| 24-W2-0420 | I Plumbing - Stainless Steel | 1 |
| 24-W4-0220 | I Paint Pump and Plumbing - Black | 1 |
| | VALVE PACKAGE - AKRON / WATEROUS - Controls Push-Pull | 1 |
| 26-C2-0000 | I SUCTION INLETS | 1 |
| 26-F2-0420 | l Suction - LPR (1) 2.5" - Swing | 1 |
| 28-00-0000 | DISCHARGE OUTLETS | 1 |
| 28-00-0220 | l All 2-1/2" Side Discharge Outlets Terminate 30-Degree Elbows | 1 |
| 28-A6-0220 | Discharge - Front Bumper w/ Swivel - thru Treadplate (PS) | 1 |
| 28-A8-0220 | Discharge - Front Bumper (1) 1.5" - Push-Pull | 1 |
| 28-F4-0220 | Speedlay - No. (1) 200' 1.75" - Double Lay - Push-Pull | 1 |
| 28-F4-1420 | Speedlay - No. (2) 200' 1.75" - Double Lay - Push-Pull | 1 |
| 28-F4-4820 | I Speedlay - No. (3) 200' 2.5" - Double Lay - Push-Pull | 1 |
| 28-F6-0620 | I Trays - (3) Slide-Out Speedlay | 1 |
| 28-F8-0820 | l Cover - End Flaps - Footman's Loop (3) Speedlays | 1 |
| 28-F8-2020 | l Color - Cover - Red | 1 |
| 28-H3-0220 | Discharge - LPF (1) 2.5" Waterous Push-Pull | 1 |
| 28-K2-8220 | Discharge - Left Panel - Aerial Waterway - Akron 4" Handwheel | 1 |
| 28-K2-9920 | Flowmeter - Pump Panel - Fire Research DFA400-040 | 1 |
| 28-K8-0220 | Discharge - RPFU (1) 2.5" Waterous Push-Pull | 1 |
| 28-L6-0220 | Discharge - RPFL (1) 3" Akron Push-Pull | 1 |
| 92-C4-2620 | Elbow - Kochek - 3" FNST X 5" Storz 30 Degree - SKE53R | 1 |
| 92-F4-0820 | Cap w/Chain - Kochek - 5" Storz - CC507 | 1 |
| 22-A1-8020 | Pump Installation - All Chassis - Midship | 1 |
| 30-C2-0220 | Foam System - Foam Pro - Hypro - 1600 | 1 |
| 24-W2-0620 | Plumbing - Stainless Steel Manifold | 1 |
| 30-M4-0620 | Flumong - Stamess Steel Manifold Flowmeter - Tee Mount w/kit - 2-1/2" | 1 |
| 30-W4-0020 30-R8-0220 | | 1 |
| | NFPA Test - Foam Proportioning Systems | 1 |
| 30-J2-2020 | Gauge - Foam A - Pump Panel - Tank Vision - WL260-A00 | 1 |
| 30-K8-4220 | Tank Switch (1) Low Level - Horizontal Mount | 1 |
| 30-R2-0620 | Placard - Operating System - Single Tank | 1 |
| 30-S2-0420 | Foam Tank (A) 15 Gallons - Polypropylene | 1 |
| 30-T2-0420 | Foam Outlet - Front Bumper Discharge | |
| 30-T2-1220 | Foam Outlet - Speedlay (1) | 1 |
| 30-T2-1420 | Foam Outlet - Speedlay (2) | |
| 40 10 0000 | == Bodies - Aerial RML 77' MVP Ext 500 Gal 1205.001 05/08/12 == | 1 |
| 40-19-0000 | WATER GAUGES | |
| 40-19-4500 | I Gauge - Tank Vision - WLA200-A00 | 1 |
| | | |

| 11/0//2012 | | Page 8 |
|------------|--|--------|
| PART NO | DESCRIPTION | QTY |
| 50-02-2200 | 500 Gallon Tank (R) - Polypropylene | 1 |
| 50-02-7300 | l Water Tank Size - NFPA Certification | 1 |
| 60-03-3350 | Body - MVP HD-77 EZ Stack | 1 |
| | Do not enclose pump panels | |
| | | |
| | LEFT SIDE | |
| | | |
| | There shall be one (1) tool compartment left side below the 1-3/4" speedlays. This compartment | |
| | shall have a vertically hinged door constructed as described above and painted job color. The interior | |
| | dimensions shall be approximately 17.5" W x 12.5" H x 28" D. The compartment shall have a | |
| | usable opening of approximately 17.5" W x 12.5" H. | |
| | | |
| | There shall be one compartment left side above the 2-1/2" speedlay. This compartment shall have a | |
| | vertically hinged door constructed as described above and painted job color. The interior dimensions | |
| | shall be approximately 11" W x 25" H x 14" D. The compartment shall have a usable opening of | |
| | approximately 11" W x 22" H. | |
| | There will/shall be one (1) compartment behind the pump panel and ahead of the rear wheels. This | |
| | compartment will/shall have a roll up door. The interior compartment dimensions will/shall be | |
| | approximately 57.5"W x 69"H x 24"D. The compartment will/shall have a useable opening of | |
| | approximately 54.5 W x 69 H x 24 D. The compartment win/shall have a useable opening of approximately 54.5 W x 60 "H. | |
| | approximately 54.5 W x 60 11. | |
| | There will/shall be one (1) compartment above the rear wheels. This compartment will/shall have a | |
| | horizontally hinged lift-up style door. The interior dimensions of the compartment will/shall be | |
| | approximately 35"W x 41"H x 24"D. The useable opening will/shall be approximately 35"W x | |
| | 39"H. | |
| | | |
| | There will/shall be one (1) compartment above the outrigger. This compartment will/shall have a | |
| | horizontally hinged lift-up style door. The interior dimensions will/shall be approximately 41"W x | |
| | 28"H x 24"D. The compartment will/shall have a useable opening of approximately 41"W x 24"H. | |
| | | |
| | There will/shall be one (1) compartment behind the outrigger. This compartment will/shall have a | |
| | roll up door. The interior dimensions of the compartment will/shall be approximately 31"W x 60"H | |
| | x 24"D. The useable opening will/shall be approximately 28"W x 47"H. | |
| | | |
| | RIGHT SIDE | |
| | | |
| | There shall be one (1) tool compartment right side below the 1-3/4" speedlays. This compartment | |
| | shall have a vertically hinged door constructed as described above and painted job color. The interior | |
| | dimensions shall be approximately 17.5" W x 12.5" H x 28" D. The compartment shall have a | |
| | usable opening of approximately 17.5" W x 12.5" H. | |
| | | |
| | There shall be one stokes compartment right side above the 2-1/2" speedlay. This compartment shall have a vertically himself door compartment as described shave and rejected in a class. The interior | |
| | have a vertically hinged door constructed as described above and painted job color. The interior | |
| | dimensions shall be approximately 11" W x 25" H x 85" D. The compartment shall have a usable | |
| | opening of approximately 11" W x 22" H. | |
| | There will/shall be one (1) compartment behind the numb panel and sheed of the man wheels. This | |
| | There will/shall be one (1) compartment behind the pump panel and ahead of the rear wheels. This | |
| | compartment will/shall have a roll up door. The interior compartment dimensions will/shall be approximately 32"W x 69"H x 24"D. The compartment will/shall have a useable opening of | |
| | approximately 29 W x 69 H x 24 D. The compartment will/shall have a useable opening of approximately 29 W x 60 H. | |
| | approximately 27 W x 00 11. | |

| 11/07/2012 | | Page 9 |
|------------|--|--------|
| PART NO | DESCRIPTION | QTY |
| | | |
| | There will/shall be one (1) compartment ahead of the rear wheels. This compartment will/shall have | |
| | a vertically hinged door. The interior compartment dimensions will/shall be approximately 21.5"W x | |
| | 28"H x 24"D. The compartment will/shall have a useable opening of approximately 21.5"W x 28"H. | |
| | There will/shall be one (1) compartment directly behind the outrigger. This compartment will/shall | |
| | have two (2) vertically hinged doors. The interior dimensions will/shall be approximately 55"W x | |
| | 28"H x 24"D. The compartment will/shall have a useable opening of approximately 55"W x 28"H. | |
| 60-03-9500 | I Access Ladder - Turntable - Left Side | 1 |
| 62-00-0420 | Torque Box - Access Panels | 1 |
| 65-00-6400 | Handrail - Aerial Access 30" (Pr.) | 1 |
| 60-24-2220 | l Compartment - Wheelwell - Air Bottles - Double Left Rear | 1 |
| 60-24-6220 | Compartment - Wheelwell - Air Bottles - Double Right Rear | 1 |
| 61-12-1220 | Pull Down Strap - Per Door | 2 |
| | L4 and L5 only | |
| | | |
| 65-00-1000 | Rubrail - Extruded Aluminum | 1 |
| 65-00-4400 | Tow Eyes - Rear - Below Body (Pr.) | 1 |
| 65-00-8205 | Handrail - 12" (ea) | 2 |
| 65-01-4500 | Cover - Hose Bed - Hypalon (U.L.) | 1 |
| 65-01-6040 | Cover - End Flaps - Footman's Loop | 1 |
| 65-01-6060 | I Cover - End Flaps - Red | 1 |
| 65-01-7000 | Divider - Hose Bed - Aerial | 1 |
| 65-01-8000 | Hose Bed Capacity - (Edit Verbiage Qty/Size/Brand) | 1 |
| 05 01 0000 | 400' of 2.5" DJ Hose | 1 |
| | 800' of 5" LDH | |
| (7.02.0000 | A P. GL. 1000 OCHWA CARD (FL.) | ~ |
| 65-02-0900 | Adj. Shelf 29-36"W x 24"D (Ea.) | 5 |
| | Mount two (2) aft of divider in L3 | |
| | Mount two (2) in R3 and one (1) in L6 | |
| 65-02-2800 | Tool Board - Vertical - 24"D x 58"H | 1 |
| 03-02-2000 | Mount forward of divider in L3 (adjustable) | 1 |
| | Would follward of divider in E3 (adjustable) | |
| 65-02-3420 | Divider - Compartment (ea) | 1 |
| 03-02-3420 | Mount 24" from forward wall in L3 | 1 |
| | Would 24 Holli fol ward wan in L5 | |
| 65-02-3500 | Step - Large Chrome-Folding Front of Body (Ea.) | 3 |
| 03-02-3300 | The steps will/shall be mounted three-(3) on the front face of the right forward compartments. | 3 |
| | The steps will/shall be mounted three-(5) on the front face of the fight forward compartments. | |
| 65-03-0700 | Trox. Poll Out 27" 48"W v 24"D (Fg.) | 1 |
| 05-05-0700 | Tray, Roll-Out, 37"-48"W x 24"D (Ea.) Mount on floor in R5 | 1 |
| | Modelit on 11001 III IC | |
| 65-03-1200 | Tray, Roll-Out, 19-36"W x 24"D - 30 Degree Tilt (ea) | 1 |
| 03-03-1200 | Mount on floor in L4 | 1 |
| | Wiodift on 11001 in L7 | |
| | == Elec. Components - Aerial RM Custom - 1205.001 05/08/12 == | 1 |
| | Elec. Components - Actiai Kivi Custom - 1203,001 03/00/12 | 1 |
| | | 1 1 |

| 11/0//2012 | | Page 10 |
|--------------------|---|---------|
| PART NO | DESCRIPTION | QTY |
| 70-00-0030 | Electrical System - (Body Only!) | 1 |
| 70-00-0450 | Load Manager / with High Idle | 1 |
| 70-00-0600 | EMI/RFI Protection | 1 |
| 70-00-0100 | Electrical, 12-Volt Testing | 1 |
| 70-00-1840 | l Whelen - Rear Mount Aerial Package 4 Super LED | 1 |
| 70-01-1200 | Whelen - LED Justice Mini Light Bars (Pr) Front of Cab | 1 |
| 70-01-5650 | Lights-Whelen-LINZ6D LED Zone A Lower Front - Split Red/White | 1 |
| | Mount one (1) each side of Ferrara logo on grille | |
| | () | |
| 70-01-6685 | Lights-Whelen-LINZ6R Linear LED Zone B & D Lower-Red | 1 |
| 70 01 0005 | Mount one (1) each side of body in rub rails under L3/R3 at forward most point and one (1) each | 1 |
| | side of body in rub rails under L6/R5 at rear most points | |
| | side of body in rub rans under Eo/R3 at real most points | |
| 70-01-7330 | Lights Wholen M7DC LED Zone C Lower Dod | 1 |
| 70-01-7330 | Lights-Whelen-M7RC LED Zone C Lower - Red | 1 |
| 10-02-3323 | Lights-Whelen-600 Super LED - Zone B & D Lower-Red | 1 |
| | Mount one (1) each side of front bumper and one (1) each side of body centered in wheel well panels | |
| 70.02.4200 | L'AL OLL CONTRACTOR | 1 |
| 70-02-4300 | Lights - Outrigger Cover Plate - (pr) Whelen TIR3 | 1 |
| | Activate with "Aerial Master" switch | |
| 7 0 02 2220 | | |
| 70-03-2320 | Beacon - Whelen RB6TRP/RB6TAP Halogen - (1) Red / (1) Amber | 1 |
| | Driver side red | |
| | | |
| | Passenger side amber | |
| | | |
| 70-04-8020 | Lights - Scene - Whelen M6ZC LED (Pr.) | 1 |
| | Mount one (1) each side of cab centered over fixed windows | |
| | | |
| | Switch lights individually from inside of cab | |
| | | |
| 70-04-8220 | Lights - Scene - Whelen M9ZC LED | 1 |
| | Mount one (1) centered over ladder compartment | |
| | | |
| | Switch light from inside of cab | |
| | | |
| 70-04-9040 | Directional Light - Whelen TAM65 - 36" Traffic Advisor | 1 |
| | Mount traffic advisor centered over ladder compartment | |
| | | |
| 70-05-3800 | Lights - LED Clearance and Maker - Truck Lite - 35001 | 1 |
| 70-05-4000 | Lights - Marker Amber (Add. Ea) | 1 |
| 70-05-4505 | Lights - Britax End/Corner - Angled LED (pr) | 1 |
| 70-05-4700 | Lights - Stop/Turn (LED) & Back-Up (Halogen) - Whelen | 1 |
| 70-05-5520 | Lights - License - LED | 1 |
| 70-06-3420 | Light - Underbody (Ea) | 4 |
| | Mount one (1) each centered under L3/R3 and L6/R5 | |
| | | |
| 70-10-0220 | Light - (1) Compartment - 8" Access Night Stik - 73008 | 2 |
| , 0 10 0220 | Mount one (1) each in L1/R1 | |
| | | |
| 70-10-0720 | Light - (1) Compartment - 18" Access Night Stik - 73018 | 5 |
| 70 10 0720 | Mount one (1) each in L2/R2, R4, and L5/R5 | 3 |
| | From the (1) each in 12/182, 187, and 12/183 | |

| 11/0//2012 | | rage 11 |
|----------------------------|--|---------|
| PART NO | DESCRIPTION | QTY |
| 70-10-1220 | Light - (1) Compartment - 28" Access Night Stik - 73028 | 1 |
| | Mount one (1) in L4 | |
| | | |
| 70-10-1820 | Light - (1) Compartment - 38" Access Night Stik - 73038 | 2 |
| | Mount two (2) in L6 | |
| | | |
| 70-10-2520 | Light - (1) Compartment - 48" Access Night Stik - 73048 | 4 |
| | Mount two (2) each in L3/R3 | |
| | | |
| 70-10-8020 | Switch - Comp. Auto Door/Ajar Indicator (ea) | 13 |
| 70-14-0200 | Back-Up Alarm | 1 |
| 71-00-3000 | Generator - Diesel - Power Tech - PT-8000 - 8.0 KW | 1 |
| 71-00-3000 | Mount generator in dunnage area | 1 |
| | Would generator in dumage area | |
| | Mount remote start/stan control in eah near driver | |
| | Mount remote start/stop control in cab near driver | |
| 71 00 5200 | | 1 |
| 71-00-5300 | Generator - Display - Fire Research (Frog D) Single Phase FDA100-008 | 1 |
| | Mount near breaker panel in L3 | |
| 5 1 00 5 500 | | |
| 71-00-5500 | Generator - Remote Oil Drain | 1 |
| 71-00-5600 | Generator - Fuel Line | 1 |
| 71-00-5700 | l Generator - Start Cable (Battery) | 1 |
| 71-00-6600 | l Generator - Cover - Alum Diamond Plate | 1 |
| 71-00-8400 | I Breaker Panel - 240/120V 12-Leg - General Electric | 1 |
| | Mount on forward wall in L3 | |
| | | |
| 72-B4-2020 | I Electrical System Testing - 120 Volt | 1 |
| 71-01-0200 | I Receptacle - 120V Twist-Lock - 20A (L5-20) ea. | 2 |
| | Mount one (1) each side of body in wheel well panels | |
| | | |
| 71-03-6000 | l Light - Flat Brow Mnt FRC Focus 750W - FCA850-S75 (each) | 2 |
| | Mount one (1) each side of cab over fixed windows | |
| | | |
| | Switch lights individually from breaker panel | |
| | | |
| 72-B2-1020 | I Cord Reel, 120V 12V DC Rewind w/ 200' 10/3 - ECR1616-17-18 | 1 |
| | Mount cord reel in R3 as high as possible | |
| | | |
| | Yellow cord | |
| | | |
| | Terminate with 20amp/120V twistlock plug | |
| | Torininate wan Zoump/120 + twistiook prag | |
| 72-B4-0220 | l Hose Rollers - Set of Four (4) | 1 |
| 72-B4-0220 72-B4-0420 | Cable Stops - Hannay - HS-3 | 1 |
| 72-B4-0420 72-B4-0620 | Cable Stops - Hailing - HS-5 | 1 |
| | | 1 |
| 80-01-0220 80-01-0820 | Body - Finish Paint - Single Color | 1 |
| | Paint - Color Body - Red - B8241EX | I |
| 80-02-1600 | Stripe - Scotchlite Triple 6" w/ 1" Top and Bottom | 1 |
| | Stripe shall "hockey stick" on body sides. | |
| | English to the state of the sta | |
| | Exact location of "hockey stick" shall be determined at pre-build conference | |

| 11/0//2012 | | rage 12 |
|------------|--|---------|
| PART NO | DESCRIPTION | QTY |
| 80-02-3060 | l Striping Color - Gold | 1 |
| 80-02-4080 | I Pin Stripe Color - Black | 1 |
| 80-03-1620 | l Stripe - Chevron Pattern - Rear Reflective | 1 |
| | Red/Yellow-Green | |
| | | |
| 80-05-0000 | Lettering Allowance | 1 |
| 90-01-1000 | NFPA Ground Ladders - Aerial | 1 |
| 92-00-0800 | l Ladder - 10' Folding Attic Alco-Lite - FL-10 | 1 |
| 92-00-2400 | I Ladder - 16' Roof Alco Lite - PRL -16 | 2 |
| 92-00-3400 | l Ladder - 14' Combination Alco Lite - CJL-14 | 1 |
| 92-00-7500 | l Ladder - 24' Extension Alco Lite - PEL-24 | 1 |
| 92-01-0000 | l Ladder - 35' Extension 3-Section Alco Lite - PEL3-35 | 1 |
| 90-23-1500 | Adapter - 4" FNST x 5" Storz Kochek - S37S54 | 1 |
| 90-22-5260 | l Cap - 5" W/Chain Kochek Storz CC507 | 1 |
| 90-36-0400 | Wheel Chock - Ziamatic SAC-44-E (PR) w/Mounting Bracket | 1 |
| 98-00-0100 | Warranty - One Yr - Mechanical Parts & Labor | 1 |
| 98-00-0600 | Warranty - Ten Yr - Structural Integrity Limited | 1 |
| 98-00-0900 | Warranty - Four Yr - Paint/Corrosion | 1 |
| 98-00-1410 | Warranty - Ten (10) Year - Stainless Steel Plumbing | 1 |
| 99-00-3920 | Transportation - Over the road | 1 |
| 99-00-4060 | l Transportation Charges | 1 |
| 99-99-3000 | FSA Fee | 1 |
| 99-99-4000 | Discount | 1 |
| 99-99-5000 | Pre-Pay Discount | 1 |
| 99-99-6000 | 100% Performance Bond | 1 |
| | == Aerial Ladder - Rear Mount 77' MVP - 1205.001 05/08/12 == | 1 |
| 68-A2-0420 | l Ladder - Rear Mount | 1 |
| 68-A6-0420 | l Specifications - Rear Mount Ladder | 1 |
| 68-B2-0420 | l Construction / Dimensions - Rear Mount Ladder | 1 |
| 68-C2-1020 | I Cover - Rungs | 1 |
| 68-C2-2020 | I Egress - Bolt-On | 1 |
| 68-C2-2220 | l Steps - Folding | 1 |
| 68-C2-2420 | I Eyelets - Rescue | 1 |
| 68-C2-4020 | l Extension Indicator Tape on Ladder | 1 |
| 68-C2-4420 | l Angle Indicator - Lighted on Base | |
| 68-C2-6420 | l Ladder Signs - Job Color | 1 |
| 68-C4-0420 | I Torque Box | 1 |
| 68-C4-6020 | Travel Support - Rear Mount Ladders | 1 |
| | Travel support located behind MVP speedlay module | |
| 60 DO 0400 | | 4 |
| 68-D2-0420 | Hydraulic System | |
| 68-D2-4020 | Hydraulic Pump - Power Take-Off | 1 |
| 68-D2-4420 | Hydraulic Pump | 1 |
| 68-D4-8020 | Hydraulic Pressure Gauge - Rear Control Station | 1 |
| 68-D4-8420 | Filter Isolation kit | 1 |
| 68-D4-8620 | Emergency Pump | 1 |
| 68-D4-8820 | Swivel - Hydraulic | 1 |
| 68-D4-9020 | Swivel - Electric | 1 |
| 68-D6-0420 | Elevation System | 1 |
| 68-D6-4220 | I Extension / Retraction System | 1 |
| | | |

| 11/0//2012 | | rage 13 |
|------------|--|---------|
| PART NO | DESCRIPTION | QTY |
| 68-D6-8020 | l Wear Pads / Bearing Surfaces | 1 |
| 68-D8-0420 | l Rotation Bearing | 1 |
| 68-D8-2220 | l Rotation Gear Box | 1 |
| 68-D8-4020 | l Tool Kit - Maintenance | 1 |
| 68-E2-0620 | I Stabilizers - Rear | 1 |
| 68-E2-4020 | l Outrigger Cylinder Stroke | 1 |
| 68-E8-0220 | I Auxiliary Stabilizer Pads (2) w/ Rack | 1 |
| 68-E4-1020 | I Stabilizer - Mechanical Locks | 1 |
| 68-E4-2040 | l Hot Dip Galvanizing | 1 |
| 68-E4-4020 | l Stabilizer - Extension System | 1 |
| 68-E4-6020 | I Stabilizer - Work Lights | 1 |
| 68-E6-0220 | l Stabilizer Arm - Warning Lights - LED | 1 |
| 68-F2-0220 | l Controls - Stabilizer - Electric/Hydraulic | 1 |
| 68-F2-1020 | l Controls - Ground Station | 1 |
| 68-F4-0820 | l Turntable - Cut-off Right Side | 1 |
| 68-F6-1320 | l Stainless Steel Safety Chain | 1 |
| 68-F6-2020 | I Controls - Turntable Console | 1 |
| 68-F6-8020 | l Load Sensing System - Automatic | 1 |
| 68-G2-0220 | l Interlock System - Aerial Stow Operation w/Indicator Light | 1 |
| 68-G2-0420 | l Interlock System - Apparatus Body Damage Control | 1 |
| 68-G2-0620 | l Interlock System - Rotation | 1 |
| 68-G2-0820 | I Retraction Safety System | 1 |
| 68-G2-1020 | l Interlock System - Cradle | 1 |
| 68-H2-0420 | I Waterway System | 1 |
| 68-H2-2220 | I Waterway Material | 1 |
| 68-H2-4420 | l Waterway - Retractable / Dual Position - Electric | 1 |
| 68-H4-0620 | Monitor - Elevated Master Stream - Akron | 1 |
| 68-H4-8020 | I Capabilities Monitor Flowing Water | 1 |
| 68-H6-6020 | I Master Stream - Controls - Tip/Turntable | 1 |
| 68-H6-8220 | Auto Stow on Aerial Monitor | 1 |
| 68-H8-2020 | I Waterway - Relief Valve | 1 |
| 68-H8-2220 | I Waterway - Dump Valve | 1 |
| 68-H8-2420 | Waterway - Drain Valve | 1 |
| 68-H8-2920 | Waterway - 4" Rear Inlet Only! - Stainless Steel | 1 |
| 68-H8-8020 | Fitting - 4" Aerial Inlet | 1 |
| 68-J2-0220 | Communication System - Two-Way | 1 |
| 68-M2-0220 | I Electrical E-Chain System | 1 |
| 68-M2-2820 | Work Lights - Turntable - LED | 1 |
| 68-M4-1020 | l Spotlights - Base Section - Unity AG (pr) | 1 |
| 68-M6-2020 | | 1 |
| 68-M8-1020 | Spotlight - Tip Section - (1) FRC Focus 500 watt - Left Side | 1 |
| | Spotlight - Tip Section - (1) Unity AG - Right Side | 1 |
| 68-N2-0220 | Receptacle - (1) 120 Volt | 1 |
| 68-P2-0420 | Lighting - Blue LED Rung Illumination | 1 |
| 68-R2-0420 | Paint - Aerial Device - FDNY Gray | 1 |
| | Match FDNY ladder color and paint process | |
| (0 D4 0220 | | 4 |
| 68-R4-0220 | I Reflective Stripe on Egress | |
| 68-S2-0420 | I Load Chart - Aerial | |
| 68-S6-0220 | l Plate - Electrocution Hazard - Pump Operator | |
| 68-S6-2020 | l Plate - Electrocution Hazard - Aerial Ladder | 1 |
| | | |

| 11/0//2012 | | Page 14 |
|------------|---|---------|
| PART NO | DESCRIPTION | QTY |
| 68-S6-2220 | l Plate - Aerial Stabilizer Motion | 1 |
| 68-S6-2420 | l Plate - Aerial Information Specification | 1 |
| 68-T2-0220 | l Testing - Third Party | 1 |
| 68-T2-4020 | I Testing - Stability | 1 |
| 68-T2-8020 | l Certificate - Inspection | 1 |
| 68-T4-0220 | I Manuals - Aerials / Platforms | 1 |
| | | 1 |
| 68-T6-0220 | l Factory Instruction - Aerials - 3 Days | 1 |
| 68-T8-0220 | l Warranty - Aerial/Platforms | 1 |
| 68-T8-2020 | l Corrosion Protection - Aerials/Platforms | 1 |
| 68-V2-0620 | l Mounting Bracket - Base Section - Pike Pole | 1 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |